



SMD Spring Coil

Fixed Coil for Surface Mounting

E1 Type

Dimensions (Unit:mm)



Electrical Characteristics

Ordering code	Wire(Φ)	I.D(Φ)	Turns / W.D	Inductance(nH)
E1 0.15-0.6-3TR	0.15	0.60	3TR	5.30
E1 0.15-0.6-4TR	0.15	0.60	4TR	6.80
E1 0.15-0.6-5TR	0.15	0.60	5TR	9.90
E1 0.15-0.6-6TR	0.15	0.60	6TR	11.9
E1 0.20-0.5-3TR	0.20	0.50	3TR	3.40
E1 0.20-0.5-4TR	0.20	0.50	4TR	4.80
E1 0.20-0.5-5TR	0.20	0.50	5TR	5.70
E1 0.20-0.5-6TR	0.20	0.50	6TR	7.30
E1 0.20-0.5-7TR	0.20	0.50	7TR	8.70
E1 0.15-0.6-3TR	0.15	0.60	3TR	5.30
E1 0.15-0.6-4TR	0.15	0.60	4TR	6.80
E1 0.15-0.6-5TR	0.15	0.60	5TR	9.90
E1 0.15-0.6-6TR	0.15	0.60	6TR	11.9
E1 0.20-0.5-3TR	0.20	0.50	3TR	3.40
E1 0.20-0.5-4TR	0.20	0.50	4TR	4.80
E1 0.20-0.5-5TR	0.20	0.50	5TR	5.70
E1 0.20-0.5-6TR	0.20	0.50	6TR	7.30
E1 0.20-0.5-7TR	0.20	0.50	7TL	8.70
E1 0.30-0.7-3TL	0.30	0.70	3TL	5.50
E1 0.30-0.7-3TL	0.30	0.70	3TL	6.00
E1 0.30-0.7-3TL	0.30	0.70	3TL	7.50
E1 0.30-0.7-4TL	0.30	0.70	4TL	11.0
E1 0.30-0.9-5TL	0.30	0.90	5TL	14.5
E1 0.30-1.0-3TL	0.30	1.00	3TL	8.00
E1 0.30-1.0-4TL	0.30	1.00	4TL	12.0
E1 0.30-1.0-5TL	0.30	1.00	5TL	16.0
E1 0.30-1.1-3TL	0.30	1.10	3TL	9.50
E1 0.30-1.1-4TL	0.30	1.10	4TL	14.0
E1 0.30-1.1-5TL	0.30	1.10	5TL	18.5
E1 0.30-1.2-4TL	0.30	1.20	4TL	15.0
E1 0.30-1.2-5TL	0.30	1.20	5TL	19.0
E1 0.30-1.3-4TL	0.30	1.30	4TL	17.0
E1 0.30-1.4-4TL	0.30	1.40	4TL	19.0

※Test Equipment

*Inductance : 4284A (1.0MHz, 500mV)

*Specifications subject to change without notice. Please check our website for latest information.

Revised 05/03/26