



SMD Spring Coil

Fixed Coil for Surface Mounting

E2 Type

Dimensions (Unit:mm)



Electrical Characteristics

Ordering code	Wire(Φ)	I.D(Φ)	Turns / W.D	Inductance(nH)
E2-0.15-0.4-3T	0.15	0.40	3T	3.60
E2-0.18-0.7-4T	0.18	0.70	4T	9.50
E2-0.18-0.7-5T	0.18	0.70	5T	12.8
E2-0.20-0.8-4T	0.20	0.80	4T	11.0
E2-0.20-0.8-5T	0.20	0.80	5T	15.0
E2-0.25-1.0-5T	0.25	1.00	5T	18.3
E2-0.25-1.8-8T	0.25	1.80	8T	77.4
E2-0.25-1.8-9T	0.25	1.80	9T	91.8
E2-0.26-1.2-3T	0.26	1.20	3T	11.0
E2-0.26-1.2-4T	0.26	1.20	4T	17.4
E2-0.26-1.2-5T	0.26	1.20	5T	22.6
E2-0.28-1.0-4T	0.28	1.00	4T	12.0
E2-0.28-1.0-5T	0.28	1.00	5T	16.0
E2-0.28-1.0-6T	0.28	1.00	6T	21.0
E2-0.28-1.1-6T	0.28	1.10	6T	24.0
E2-0.30-1.0-3T	0.30	1.00	3T	9.00
E2-0.30-1.0-4T	0.30	1.00	4T	12.0
E2-0.30-1.0-5T	0.30	1.00	5T	15.0
E2-0.32-1.0-3T	0.32	1.00	3T	8.00
E2-0.35-1.4-5T	0.35	1.40	5T	23.0
E2-0.35-1.6-4T	0.35	1.60	4T	21.0
E2-0.35-1.6-5T	0.35	1.60	5T	28.0
E2-0.40-1.5-4T	0.40	1.50	4T	19.6
E2-0.40-1.5-5T	0.40	1.50	5T	24.0
E2-0.40-1.5-6T	0.40	1.50	6T	31.0
E2-0.40-3.0-8T	0.40	3.00	8T	128.5
E2-0.40-3.0-9T	0.40	3.00	9T	150.0
E2-0.4-3.0-10T	0.40	3.00	10T	174.0
E2-0.45-1.4-3T	0.45	1.40	3T	11.0
E2-0.45-1.4-4T	0.45	1.40	4T	15.0
E2-0.45-1.5-5T	0.45	1.50	5T	23.2
E2-0.50-2.0-5T	0.50	2.00	5T	34.4
E2-0.50-2.0-6T	0.50	2.00	6T	42.7
E2-0.60-2.6-5T	0.60	2.60	5T	44.8
E2-0.80-3.0-6T	0.80	3.00	6T	61.5

※Test Equipment

*Inductance : 4284A (1.0MHz, 500mV)

*Specifications subject to change without notice. Please check our website for latest information.

Revised 05/03/26